M8 female 0° A-cod. screw terminal

4-pol., 0,14 - 0.5mm², 2,5 - 5mm


Art.No.: 7000-08631-0000000
Weight: 0,020 kg
Country of origin: CN
Model designation: M8 BUCHSE GER. 2,5..5 4pol.


Female straight
M8, 4-pole
Screw terminal
Connection cross section: 0.14...0.5 mm²


Link to Product

Illustration









Product may differ from Image

Side 1-1

Family construction form	M8
No. of poles	4
Coding	A

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

Gender	female
Mounting method	inserted, screwed
Tightening torque	0.4 Nm
Width across flats	SW13
Cable outlet	straight
Material contact	Brass
Coating contact	gold plated
Degree of protection (EN IEC 60529)	IP67
Side 2-2	
Mounting method	Field-wireable
Commercial data	
URL Webshop	https://shop.murrelektronik.com/7000-08631-0000000
GTIN	4048879224505
EU-Customs tariff number	85366990
US-Customs tariff number	8536694020
ECLASS-6.0	27279221
ECLASS-6.1	27260702
ECLASS-7.0	27440102
ECLASS-7.1	27440102
ECLASS-8.0	27440102
ECLASS-8.1	27440102
ECLASS-9.0	27440116
ECLASS-9.1	27440106
ECLASS-10.0.1	27440106
ECLASS-10.1	27440102
ECLASS-11.0	27440106
ECLASS-11.1	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440106
ECLASS-14.0	27440106
ETIM-5.0	EC002635
ETIM-6.0	EC002635
ETIM-7.0	EC002635
ETIM-8.0	EC002635
ETIM-9.0	EC002635
ETIM-10.0	EC002635
customs tariff number	85366990
EAN	4048879224505
Packaging unit	1
Electrical data | Supply	
Operating voltage AC max.	50 V
Operating voltage DC max.	60 V
Current operating per contact max.	4 A
Installation	
Connection cross section min.	0.14 mm²
Connection cross section max.	0.5 mm²
Installation | Connection	
Connection	Screw terminals SK
Installation | Pin assignment	
Coding	A
Device protection | Electrical	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

Additional condition protection degree	inserted, screwed
Pollution Degree	3
Overvoltage category (EN 60664-1)	III
Overvoltage category (EN 60950-1)	II
Insulation resistance min.	100 mΩ
Mechanical data | Material data	
housing	PBT
Material contact carrier	PA66
Mechanical data | Mounting data	
Height	45 mm
Width	12 mm
Depth	12 mm
Clamping range min.	2.5 mm
Clamping range max.	5 mm
Environmental characteristics | Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	85 °C
Important installation notes	
Note on bending radius	**Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15