ECO-RAIL-2 POWER SUPPLY 1-PHASE,

IN: 90 ... 132 VAC / 173 … 264 VAC OUT: 24V/10ADC


Art.No.: 85135
Weight: 0,900 kg
Country of origin: CN
Model designation: Eco-Rail-2 10-100-240/24

INPUT: 90...132 V AC/173...264 V AC
OUTPUT: 23...28 V DC
Current: 10 A
Mains failure bridging min.
min. 12 ms (115 V AC); min. 30 ms (230 V AC)

Link to Product

Illustration





Product may differ from Image

Commercial data

URL Webshop	https://shop.murrelektronik.com/85135
GTIN	4048879694483
EU-Customs tariff number	85044083
US-Customs tariff number	8504409550
ECLASS-6.0	27049002
ECLASS-6.1	27049002
ECLASS-7.0	27049002
ECLASS-7.1	27049002
ECLASS-8.0	27049002
ECLASS-8.1	27049002
ECLASS-9.0	27040701
ECLASS-9.1	27040701
ECLASS-10.0.1	27040701
ECLASS-10.1	27040701
ECLASS-11.0	27040701
ECLASS-11.1	27040701

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

ECLASS-12.0	27040701
ECLASS-13.0	27040701
ECLASS-14.0	27040701
ETIM-5.0	EC002540
ETIM-6.0	EC002540
ETIM-7.0	EC002540
ETIM-8.0	EC002540
ETIM-9.0	EC002540
ETIM-10.0	EC002540
customs tariff number	85044083
EAN	4048879694483
Packaging unit	1
Electrical data	
Parallel connection	No
Series connection	Yes
Number of devices series connection max.	2
Electrical data | Supply	
Power frequency	50 ... 60 Hz
Electrical data | Input	
Nominal input voltage AC	100 V … 240 V
Input voltage 1 AC min.	90 V
Input voltage 1 AC max.	132 V
Input voltage 2 AC min.	173 V
Input voltage 2 AC max.	264 V
Nominal current AC	4.3 A @ 100 V,2.1 A @ 240 V
Inrush current max.	18 A @ 230 V
Efficiency	86 % @ 115 V AC 87 % @ 230 V AC
Characteristic back-up fuse	Inertia
Fuse protection primary side internal	5 A
Electrical data | Output	
Output voltage adjustable	Yes
Output voltage DC	24 V
Output voltage DC min.	23 V
Output voltage DC max.	28 V
Output current	10 A
Spikes (s-s) max.	50 mV
Ripple effective max.	10 mV
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP20
Overload protection output	Yes
Short-circuit protection output	Yes
Mechanical data | Mounting data	
Height	125 mm
Width	68 mm
Depth	125 mm
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Environmental characteristics | Electromagnetic compatibility	
Interference emission	IEC 61000-3-2
Environmental characteristics | Climatic	
Operating temperature min.	0 °C

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Operating temperature max.	40 °C
Derating	40 °C
Ambient temperature (storage, transport)	-20 °C … 85 °C
Relative humidity (operation)	20 % … 90 %
Additional condition relative humidity	no condensation
Conformity	
Product standard	EN IEC 61010-2-201
Connection type 2-2	
Family construction form	terminal
No. of poles	3
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	PE
PIN 2	N
PIN 3	L
Family construction form	terminal
No. of poles	4
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	-
PIN 2	-
PIN 3	+
PIN 4	+

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14