MCS-B POWER SUPPLY 1-PHASE,

IN: 100-265VAC OUT: 24V/10ADC


Art.No.: 85165
Weight: 0,831 kg
Country of origin: CZ
Model designation: MCS-B 10-110-240/24


INPUT: 100...265 V AC
OUTPUT: 24 V DC +3/-1%
Current: 10 A
Mains failure bridging min.
min. 15 ms (115 V AC); min. 115 ms (230 V AC)

Link to Product

Illustration







Product may differ from Image

Commercial data

URL Webshop	https://shop.murrelektronik.com/85165
GTIN	4048879080354

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

EU-Customs tariff number	85044083
US-Customs tariff number	8504409550
ECLASS-6.0	27049002
ECLASS-6.1	27049002
ECLASS-7.0	27049002
ECLASS-7.1	27049002
ECLASS-8.0	27049002
ECLASS-8.1	27049002
ECLASS-9.0	27040701
ECLASS-9.1	27040701
ECLASS-10.0.1	27040701
ECLASS-10.1	27040701
ECLASS-11.0	27040701
ECLASS-11.1	27040701
ECLASS-12.0	27040701
ECLASS-13.0	27040701
ECLASS-14.0	27040701
ETIM-5.0	EC002540
ETIM-6.0	EC002540
ETIM-7.0	EC002540
ETIM-8.0	EC002540
ETIM-9.0	EC002540
ETIM-10.0	EC002540
customs tariff number	85044083
EAN	4048879080354
Packaging unit	1
Electrical data	
Parallel connection	Yes
Number of devices parallel connection max.	5
Series connection	Yes
Number of devices series connection max.	2
Electrical data | Supply	
Protective measure	SELV
Power frequency	50 ... 60 Hz
Electrical data | Input	
Input voltage AC min.	100 V
Input voltage AC max.	265 V
Nominal input voltage AC	115 V … 230 V
Nominal current AC	3.4 A @ 115 V,2.2 A @ 230 V
Inrush current max.	40 A
Efficiency	83 % @ 115 V AC 85 % @ 230 V AC
External back-up fuse per phase max.	16 A
Electrical data | Output	
Output voltage adjustable	Yes
Output voltage DC	24 V
Output voltage DC min.	22 V
Output voltage DC max.	28 V
Output current	10 A
Spikes (s-s) max.	100 mV
Ripple effective max.	20 mV
Device protection | Electrical	
Overload protection output	Yes

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Short-circuit protection output	Yes
Mechanical data | Mounting data	
Height	128 mm
Width	68 mm
Depth	165 mm
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Environmental characteristics | Electromagnetic compatibility	
Interference emission	EN 55011
Environmental characteristics | Climatic	
Operating temperature min.	-25 °C
Operating temperature max.	40 °C
Derating	40 °C
Ambient temperature (storage, transport)	-25 °C … 85 °C
Relative humidity (operation)	5 % … 95 %
Additional condition relative humidity	no condensation
Conformity	
Product standard	EN IEC 61010-2-201, EN 61204-3
Connection type 2-2	
Family construction form	terminal
No. of poles	3
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	PE
PIN 2	N
PIN 3	L
Family construction form	terminal
No. of poles	4
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	-
PIN 2	-
PIN 3	+
PIN 4	+

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14