## M12 male 90° A-cod. screw terminal

5-pol., max. 0,75mm², 4 - 6mm, shielded


Art.No.: 7000-13341-0000000
Weight: 0,058 kg
Country of origin: HU
Model designation: M12 STECKER GEW.4..6 5pol.


Male 90°
M12, 5-pole
Shielded
Sealing range (cable Ø): 4...6 mm


Link to Product

### Illustration






Product may differ from Image

### Side 1-1

| | |
|---|---|
| Family construction form | M12 |
| No. of poles | 5 |
| Coding | A |
| Gender | male |
| Mounting method | inserted, screwed |
| Tightening torque | 0.6 Nm |
| Width across flats | SW18 |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

| | |
|---|---|
| Cable outlet | angled |
| Material contact | Brass |
| Coating contact | gold plated |
| Degree of protection (EN IEC 60529) | IP67 |
| **Side 2-2** | |
| Mounting method | Field-wireable |
| **Commercial data** | |
| URL Webshop | https://shop.murrelektronik.com/7000-13341-0000000 |
| EU-Customs tariff number | 85366990 |
| US-Customs tariff number | 8536694020 |
| ETIM-9.0 | EC002635 |
| ETIM-10.0 | EC002635 |
| customs tariff number | 85366990 |
| EAN | 4048879198820 |
| Packaging unit | 1 |
| **Electrical data \| Supply** | |
| Operating voltage AC max. | 60 V |
| Operating voltage DC max. | 60 V |
| Current operating per contact max. | 4 A |
| **Installation** | |
| Connection cross section max. | 0.75 mm² |
| **Device protection** | |
| Shielded | Yes |
| **Device protection \| Electrical** | |
| Additional condition protection degree | inserted, screwed |
| Pollution Degree | 3 |
| Overvoltage category (EN 60950-1) | II |
| Rated surge voltage | 1.5 kV |
| Material group (IEC 60664-1) | III |
| **Mechanical data \| Material data** | |
| housing | Zinc die-casting |
| Coating housing | nickel plated |
| **Mechanical data \| Mounting data** | |
| Mounting method | inserted, screwed |
| Clamping range min. | 4 mm |
| Clamping range max. | 6 mm |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -40 °C |
| Operating temperature max. | 85 °C |
| **Important installation notes** | |
| Note on bending radius | **Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |
| Note on strain relief | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties. |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15