Emparro IP67 Power Supply 1-Phase

OUT: 24VDC 4A - 7/8" 5P - SELV


Art.No.: 9000-11112-1962020
Weight: 1,100 kg
Country of origin: CZ
Model designation: Emparro67 4-100-240/24 7/8"-7/8"

Emparro®67
INPUT: 90...265 V AC/90...265 V DC
OUTPUT: 24 V DC (SELV), ±2%
Current: 4 A

[Link to Product]

Illustration





Product may differ from Image

Commercial data

URL Webshop	https://shop.murrelektronik.com/9000-11112-1962020
GTIN	4048879482660
EU-Customs tariff number	85044095
US-Customs tariff number	8504409580
ECLASS-6.0	27049002
ECLASS-6.1	27049002
ECLASS-7.0	27049002
ECLASS-7.1	27049002
ECLASS-8.0	27049002
ECLASS-8.1	27049002
ECLASS-9.0	27040701
ECLASS-9.1	27040701
ECLASS-10.0.1	27040701
ECLASS-10.1	27040701
ECLASS-11.0	27040701
ECLASS-11.1	27040701
ECLASS-12.0	27040701
ECLASS-13.0	27040701

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

ECLASS-14.0	27040701
ETIM-5.0	EC002540
ETIM-6.0	EC002540
ETIM-7.0	EC002540
ETIM-8.0	EC002540
ETIM-9.0	EC002540
ETIM-10.0	EC002540
customs tariff number	85044095
EAN	4048879482660
Packaging unit	1
Electrical data	
Parallel connection	Yes
Number of devices parallel connection max.	3
Series connection	Yes
Number of devices series connection max.	2
Electrical data | Supply	
Protective measure	SELV
Power frequency	50 ... 60 Hz
Electrical data | Input	
Input voltage AC min.	90 V
Input voltage AC max.	265 V
Nominal input voltage AC	100 V … 240 V
Input voltage DC min.	90 V
Input voltage DC max.	265 V
Nominal current AC	1.1 A @ 100 V,0.5 A @ 240 V
Inrush current max.	8.9 A @ 230 V
Power factor	230 V AC
Efficiency	91.7 % @ 115 V AC 92.4 % @ 230 V AC
Characteristic back-up fuse	Inertia
Fuse protection primary side internal	6.3 A
Electrical data | Output	
Output voltage adjustable	No
Output voltage DC	24 V
Output voltage DC min.	23.52 V
Output voltage DC max.	24.48 V
Output current	4 A
Mains failure bridging min.	45 ms @ 230 V AC
Power Boost	150 %
Duration Power Boost min.	5 s
Spikes (s-s) max.	100 mV
Ripple effective max.	20 mV
Device protection | Electrical	
Degree of protection (EN IEC 60529)	IP67
Overload protection output	Yes
Short-circuit protection output	Yes
Overtemperature protection output	Yes
Mechanical data | Mounting data	
Height	51 mm
Width	109 mm
Depth	140 mm
Suitable for mounting type	6 hole screw mounting
Environmental characteristics | Electromagnetic compatibility	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Interference emission	EN IEC 55011, IEC 61000-3-2
Environmental characteristics | Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	60 °C
Derating	min. 60 °C
Ambient temperature (storage, transport)	-40 °C … 80 °C
Relative humidity (operation)	4 % … 100 %
Conformity	
Product standard	EN IEC 61010-2-201, EN 61204-3
Connection type 1-1	
Connection type 1	Output
Family construction form	7/8"
No. of poles	5
Gender	female
Color contact carrier	black
PIN 1	0 V DC
PIN 2	0 V DC
PIN 3	PE
PIN 4	24 V DC
PIN 5	24 V DC

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14