M12 male 0° A-cod. Push-Lock

5-pol., 0,08 - 0,75mm², 4 - 8mm


Art.No.: 7000-13901-0000000
Weight: 0,022 kg
Country of origin: DE
Model designation: MSAL0-U-Push-Lock


Male straight
M12, 5-pole
A-coded
Push-Lock-connection
Sealing range (cable Ø): 4...8 mm
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

Link to Product

Illustration







Product may differ from Image

Side 1-1

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

Family construction form	M12
No. of poles	5
Coding	A
Gender	male
Mounting method	inserted, screwed
Threaded hole	M12 x 1
Tightening torque	0.4 Nm
Cable outlet	straight
Material contact	Bronze
Degree of protection (EN IEC 60529)	IP67, IP65
Side 2-2	
Family construction form	Push-Lock spring clamp connection
Mounting method	Field-wireable
Commercial data	
URL Webshop	https://shop.murrelektronik.com/7000-13901-0000000
GTIN	4065909028926
EU-Customs tariff number	85366990
US-Customs tariff number	8536694020
ECLASS-6.0	27279218
ECLASS-6.1	27279218
ECLASS-7.0	27279218
ECLASS-7.1	27279218
ECLASS-8.0	27279218
ECLASS-8.1	27279218
ECLASS-9.0	27060312
ECLASS-10.0.1	27060312
ECLASS-10.1	27060312
ECLASS-11.0	27060312
ECLASS-11.1	27060312
ECLASS-12.0	27060312
ECLASS-13.0	27060312
ECLASS-14.0	27060312
ETIM-5.0	EC002635
ETIM-6.0	EC002635
ETIM-7.0	EC002635
ETIM-8.0	EC002635
ETIM-9.0	EC002635
ETIM-10.0	EC002635
customs tariff number	85366990
EAN	4065909028926
Packaging unit	1
Electrical data | Supply	
Operating voltage AC	48 V
Operating voltage DC	60 V
Operating voltage AC max. (UL-listed)	250 V
Current operating per contact (UL)	4 A
Diagnostics	
Status indication LED	No
Installation	
Cross section connection with wire end ferrule min.	0.14 mm²
Cross section connection with wire end ferrule max.	0.5 mm²

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

Cross section connection with wire end ferrule AWG min.	26 AWG
Cross section connection with wire end ferrule AWG max.	20 AWG
Cross section connection without wire end ferrule min.	0.14 mm²
Cross section connection without wire end ferrule max.	0.75 mm²
Cross section connection without wire end ferrule AWG min.	26 AWG
Cross section connection without wire end ferrule AWG max.	18 AWG
Installation | Connection	
Mating cycles min.	100
Connection information	Push-Lock spring clamp connection
Installation | Pin assignment	
Coding	A
Device protection | Electrical	
Additional condition protection degree	inserted, screwed
Pollution Degree	3
Overvoltage category (EN 60950-1)	II
Insulation resistance min.	100 mΩ
Mechanical data | Material data	
housing	PA
Material contact carrier	PA66
Coating contact	gold plated
Gasket	NBR
Combustibility class (UL94)	V-0
Mechanical data | Mounting data	
Mounting method	inserted, screwed, Shaking protection
Clamping range min.	4 mm
Clamping range max.	8 mm
Environmental characteristics | Climatic	
Operating temperature min.	-40 °C
Operating temperature max.	85 °C
Important installation notes	
Note on bending radius	**Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces.
Note on strain relief	Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties.
Conformity	
Product standard	EN IEC 61076-2-101 (M12)

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15