## M12 female 0° A-cod. IDC

3-pol., 0.5 - 1.0mm², 5,5 - 8mm


Art.No.: 7000-12621-0000000
Weight: 0,020 kg
Country of origin: DE
Model designation: MSBL0-AF-W-IDC


Female straight
M12, 3-pole
IDC terminals
Connection cross section: 0.5...1.0 mm²
Art-No. 7005 - M12 Lite - (plastic hexagonal screw) on request
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.


**Link to Product**

**Illustration**






Product may differ from Image

**Side 1-1**

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

| | |
|---|---|
| Family construction form | M12 |
| Degree of protection (EN IEC 60529) | IP67 |
| **Commercial data** | |
| URL Webshop | https://shop.murrelektronik.com/7000-12621-0000000 |
| GTIN | 4048879201735 |
| EU-Customs tariff number | 85366990 |
| US-Customs tariff number | 8536694020 |
| ECLASS-6.0 | 27279221 |
| ECLASS-6.1 | 27260702 |
| ECLASS-7.0 | 27440102 |
| ECLASS-7.1 | 27440102 |
| ECLASS-8.0 | 27440102 |
| ECLASS-8.1 | 27440102 |
| ECLASS-9.0 | 27440116 |
| ECLASS-9.1 | 27440106 |
| ECLASS-10.0.1 | 27440106 |
| ECLASS-10.1 | 27440102 |
| ECLASS-11.0 | 27440106 |
| ECLASS-11.1 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440106 |
| ECLASS-14.0 | 27440106 |
| ETIM-5.0 | EC002635 |
| ETIM-6.0 | EC002635 |
| ETIM-7.0 | EC002635 |
| ETIM-8.0 | EC002635 |
| ETIM-9.0 | EC002635 |
| ETIM-10.0 | EC002635 |
| customs tariff number | 85366990 |
| EAN | 4048879201735 |
| Packaging unit | 1 |
| **Electrical data \| Supply** | |
| Operating voltage AC max. | 32 V |
| Operating voltage DC max. | 32 V |
| Current operating per contact max. | 4 A |
| **Installation** | |
| Single wire diameter min. | 0.1 mm |
| Connection cross section min. | 0.5 mm² |
| Connection cross section max. | 1 mm² |
| **Installation \| Connection** | |
| Tightening torque | 0.6 Nm |
| Wire insulation diameter min. | 1.6 mm |
| Wire insulation diameter max. | 2 mm |
| **Device protection \| Electrical** | |
| Additional condition protection degree | inserted, screwed |
| **Mechanical data \| Mounting data** | |
| Height | 55 mm |
| Width | 22 mm |
| Depth | 22 mm |
| Mounting method | inserted, screwed, Shaking protection |
| Clamping range min. | 5.5 mm |
| Clamping range max. | 8 mm |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15

| | |
|---|---|
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -25 °C |
| Operating temperature max. | 85 °C |
| **Important installation notes** | |
| Note on bending radius | **Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |
| Note on strain relief | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties. |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-15