IMPACT67 PN DO16 M12L 5P galvanic separation

PROFINET, compact module


Art.No.: 55175
Weight: 0,486 kg
Country of origin: DE
Model designation: IMPACT67 PN DO16 M12L 5P


Digital outputs
DO16 (IRT)
Ethernet 10/100 Mbit/s; M12, D-coded
M12 power, 5-pin, L-coded, 2× max. 12 A
M12, 5-pole, A-coded
Fast-Start-Up (FSU)
Galvanic isolation
Connection cables are in the online shop under "Connection Technology".
Housing fully potted.


Link to Product

Illustration










The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14



Product may differ from Image

Commercial data	
URL Webshop	https://shop.murrelektronik.com/55175
GTIN	4065909225233
EU-Customs tariff number	85389099
US-Customs tariff number	8538908180
ECLASS-6.1	27242604
ECLASS-7.0	27242604
ECLASS-7.1	27242604
ECLASS-8.0	27242604
ECLASS-8.1	27242604
ECLASS-9.0	27242604
ECLASS-9.1	27242604
ECLASS-10.0.1	27242604
ECLASS-10.1	27242604
ECLASS-11.0	27242604
ECLASS-11.1	27242604
ECLASS-12.0	27242604
ECLASS-13.0	27242604
ECLASS-14.0	27242604
customs tariff number	85389099
EAN	4065909225233
Packaging unit	1
Electrical data | Supply	
Norm operating voltage	IEC/EN 61131-2
Operating voltage US DC	24 V
Total current US max.	12 A
Operating voltage UA DC	24 V
Total current UA max.	12 A
Idle current max.	130 mA
Actuator current UA	max. 12 A
Sensor current	max. 12 A
Electrical data | Output	
Output current per pin max.	2 A

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Overload resistant	Yes
Short-circuit protected	Yes
Switching frequency max.	50 Hz
Industrial communication | Bus data	
Supported protocol	PROFINET
Industrial communication | PROFINET	
Conformance Class	C
addressing	DCP
PROFIenergy	Yes
Netload Class	III
Specification	V2.3
Cycle time min.	1 ms
IRT-network communication	Yes
IRT-application	No
MRP client	Yes
Fast-Start-Up (FSU)	Yes
Fast start up time max.	500 s
Shared device/input	Yes
Diagnostics	
Actuator warning	per channel via LED and BUS
Cable break	per port
Diagnostic	No voltage, Under voltage
Diagnostic via BUS	per module and channel
Diagnostic via LED	per module and channel
LED display	Ethernet connection/data traffic
Device protection | Electrical	
Installation height max. ASL	3000 m
Degree of protection (EN IEC 60529)	IP67
Protection class (EN IEC 61140)	III
Additional condition protection class	Power supply must comply with SELV or PELV
Invers-polarity protection	Yes
Pollution Degree	2
Over voltage protection	Yes
Overload protection device supply	Yes
Short-circuit protection output	electronic
Galvanic separation US/UA	Yes
Device protection | Mechanical	
Shock resistance (EN IEC 60068-2-27)	15 g 11 ms
Mechanical data | Material data	
housing	PBT, PC
Mechanical data | Mounting data	
Net weight	486 g
Height	225.4 mm
Width	63 mm
Depth	36 mm
Suitable for mounting type	2-hole screw mounting
Environmental characteristics | Electromagnetic compatibility	
Interference emission	EN 55016-2-3
Immunity to interference	EN/IEC 61000-4-2, EN IEC 61000-4-3, EN/IEC 61000-4-4, EN/IEC 61000-4-5, EN IEC 61000-4-6
Environmental characteristics | Climatic	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Ambient temperature (operation)	-25 °C … 55 °C
Ambient temperature (storage, transport)	-25 °C … 70 °C
Relative humidity (operation)	95 %
Relative humidity (storage, transport)	max. 95 %
Technical Data | Reliability	
MTTF (EN/IEC 61709, EN ISO 13849-1, SN 29500)	63 a @ 40 °C
Environmental product conformity	
REACH ((EC) 1907/2006)	compliant
RoHS (2011/65/EU, (EU) 2015/863)	compliant
RoHS-Exemption (2011/65/EU)	6(c), 7(c)-I
China RoHS (SJ/T 11364, GB/T 26572)	EFUP-25
WEEE (2012/19/EU)	compliant
Conformity	
Product standard	EN 61131-2
CE	2014/30/EU, 2011/65/EU
UKCA	The Electromagnetic Compatibility Regulations 2016, The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012
Approvals	
UL Listed (US, CA)	E201820
UL-Standard	UL 61010-2-201, UL 61010-1
CSA-Standard	CAN/CSA-C22.2 No. 61010-2-201, CAN/CSA-C22.2 No. 61010-1-12
Connection type 4-4	
Connection type 1	X0-X7
Connection type 2	XD1
Connection type 3	XD2
Connection type 4	XF1, XF2
Family construction form	M12
No. of poles	5
Coding	A
Gender	female
Color contact carrier	black
PIN 1	n.c.
PIN 2	DO (UA)
PIN 3	0 V (UA)
PIN 4	DO (UA)
PIN 5	PE
Family construction form	M12
No. of poles	5
Coding	L
Gender	male
Color contact carrier	black
PIN 1	24 V DC (US)
PIN 2	0 V (UA)
PIN 3	0 V (US)
PIN 4	24 V DC (UA)
PIN 5	PE
Family construction form	M12
No. of poles	5
Coding	L
Gender	female
Color contact carrier	black

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

PIN 1	24 V DC (US)
PIN 2	0 V (UA)
PIN 3	0 V (US)
PIN 4	24 V DC (UA)
PIN 5	PE
Family construction form	M12
No. of poles	4
Coding	D
Gender	female
Color contact carrier	black
Mounting method	inserted, screwed
Tightening torque	0.6 Nm
PIN 1	TD +
PIN 2	RD +
PIN 3	TD -
PIN 4	RD -
PIN 5	n.c.

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14