MCS POWER SUPPLY 1-PHASE,

IN: 95-132VAC OUT: 24-28V/20ADC


Art.No.: 85088
Weight: 2,100 kg
Country of origin: CZ
Model designation: MCS 20-115/24


INPUT: 95...132 V AC
OUTPUT: 24...28 V DC
Current: 20 A

Link to Product

Illustration







Product may differ from Image

Commercial data

URL Webshop	https://shop.murrelektronik.com/85088
GTIN	4048879080491
EU-Customs tariff number	85044083
US-Customs tariff number	8504409550

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

ECLASS-6.0	27049002
ECLASS-6.1	27049002
ECLASS-7.0	27049002
ECLASS-7.1	27049002
ECLASS-8.0	27049002
ECLASS-8.1	27049002
ECLASS-9.0	27040701
ECLASS-9.1	27040701
ECLASS-10.0.1	27040701
ECLASS-10.1	27040701
ECLASS-11.0	27040701
ECLASS-11.1	27040701
ECLASS-12.0	27040701
ECLASS-13.0	27040701
ECLASS-14.0	27040701
ETIM-5.0	EC002540
ETIM-6.0	EC002540
ETIM-7.0	EC002540
ETIM-8.0	EC002540
ETIM-9.0	EC002540
ETIM-10.0	EC002540
customs tariff number	85044083
EAN	4048879080491
Packaging unit	1
Electrical data	
Parallel connection	Yes
Series connection	Yes
Electrical data | Supply	
Protective measure	SELV
Power frequency	50 ... 60 Hz
Electrical data | Input	
Input voltage AC	115 V
Input voltage AC min.	95 V
Input voltage AC max.	132 V
Current input AC	8,4 A
Efficiency	90 %
External back-up fuse per phase max.	16 A
Electrical data | Output	
Output voltage adjustable	Yes
Output voltage DC	24 V
Output voltage DC min.	24 V
Output voltage DC max.	28 V
Output current	20 A
Output current (UL)	24 A
Selectable switch-off mode	front sided plug link (automatic re-start or definite shut-off)
Mains failure bridging min.	20 ms @ 115 V AC
Spikes (s-s) max.	250 mV
Ripple effective max.	20 mV
Device protection | Electrical	
Overload protection output	Yes
Short-circuit protection output	Yes
Mechanical data | Mounting data	

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

Height	170 mm
Width	84 mm
Depth	201 mm
Mounting method	geschnappt
Suitable for mounting type	Mounting rail TH35, (EN 60715)
Environmental characteristics | Electromagnetic compatibility	
Interference emission	IEC/EN 55022
Environmental characteristics | Climatic	
Operating temperature min.	0 °C
Operating temperature max.	60 °C
Ambient temperature (storage, transport)	-25 °C … 85 °C
Relative humidity (operation)	5 % … 95 %
Additional condition relative humidity	no condensation
Conformity	
Product standard	EN IEC 61010-2-201, EN 61204-3
Connection type 2-2	
Family construction form	terminal
No. of poles	3
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	PE
PIN 2	N
PIN 3	L
Family construction form	terminal
No. of poles	4
Gender	female
Color contact carrier	green
Connection	Spring clamp terminals FK
PIN 1	-
PIN 2	-
PIN 3	+
PIN 4	+

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14