
I/O modules

BNI IOL-728-S51-P012
Order Code: BNI00FA



Basic features

Approval/Conformity	CE WEEE Ecolab cULus UKCA
Scope of delivery	Grounding strap M4x6 screw Short guide
Secondary features for condition monitoring	Vibration monitoring Internal temperature monitoring
Style	Two-row

Display/Operation

IO-Link communication indicator	yes
Module supply indicator	yes
Sensor supply US indicator	yes

Electrical connection

Connection (COM 1)	M12x1-Male, 4-pin, A-coded
Connection slots	8x M12x1-Female, 5-pin, A-coded
Contact, surface protection	NiAu

Electrical data

Current consumption without load, max.	60 mA
Current sum US, sensor	4 A
IO-Link function	Device
IO-Link ports, number	1
Operating voltage Ub	18...30.2 VDC
Rated operating voltage Ue DC	24 V

Environmental conditions

Ambient temperature	-25...70 °C
IP rating	IP68, IP69K, when threaded in
Storage temperature	-25...70 °C
Temperature coefficient typ.	±0.01 %/K

Functional safety

MTTF (40 °C)	50.1 a

IO-Link

IO-Link Profil IDs	0x4000 Identification and Diagnosis

I/O modules

BNI IOL-728-S51-P012
Order Code: BNI00FA

Interface

Additional function	Vibration Internal temperature Device discovery
Analog inputs	8x Analog, voltage/analog, current (0…10 V/-10…10 V/0…5 V/-5…5 V/ 5…10 V/4…20 mA/0…20 mA)
Cycle time min.	3 ms
IO-Link version	1.1
Interface	IO-Link 1.1
Process data IN	23 bytes
Process data cycle min.	3 ms
Single-channel monitoring	yes
Transfer rate	COM3 (230.4 kBaud)

Material

Gasket, material	FKM NBR
Housing material	PBT, GF30 1.4404 stainless steel, Inserts
Housing shield	no

Mechanical data

Dimension	68 x 38.3 x 183.5 mm
Mounting ground strap	M4 internal thread
Mounting part	2-hole screw mount
Weight	496 g

Range/Distance

Resolution	≤ 16 Bit Adjustable


Remarks

See short guide and/or Manual


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



IO-Link
PIN 1: +24V
PIN 2: n.c.
PIN 3: GND
PIN 4: C/Q, IO-Link DC-Channel



Analog input port
PIN 1: +24V, 200mA
PIN 2: Input 2
PIN 3: GND
PIN 4: Input 1
PIN 5: Function ground