
Network Blocks

BNI XG1-505-0A5-K083
Order Code: BNI00HP



Basic features

Approval/Conformity	CE UKCA WEEE cULus
Display	no
Not incl. in scope of delivery	Label plates Port cover
Safety Hub Support	no
Scope of delivery	Grounding strap
Style	Two-row
Supported web browsers	Google Chrome Mozilla Firefox Microsoft Edge

Display/Operation

IO-Link communication indicator	LED green
Sensor supply US indicator	LED green
Switching function display	LED yellow

Electrical connection

Connection (COM 1)	M12x1-Female, 4-pin, D-coded
Connection (COM 2)	M12x1-Female, 4-pin, D-coded
Connection (supply voltage IN)	M12x1-Male, 2-pin, A-coded
Connection slots	8x M12x1-Female, 5-pin, A-coded
Contact, surface protection	CuSnZn2 on I/O ports NiAU on power and communication ports

Electrical data

Address range	IPV4
Configurable inputs/outputs	yes
Current max. Pin 1/L+	0.5 A
Current sum US, sensor	4.0 A
IO-Link function	Master
Operating voltage Ub	18...30 VDC
Output current max.	250 mA short-circuit proof and overload-proof
Output current max. Pin 4	0.25 A
Output current max. per port (Class A)	0.75 A
Rated operating voltage Ue DC	24 V
Transfer rate	10/100 Mbit/s

Network Blocks

BNI XG1-505-0A5-K083
Order Code: BNI00HP

Environmental conditions

Ambient temperature	-25...55 °C
EN 60068-2-27, Continuous shock	15 g, 2 ms
EN 60068-2-27, Shock	15 g, 6 ms
EN 60068-2-6, Vibration	5…61 Hz, constant amplitude 1 mm 61…500 Hz, constant acceleration 15 g
IP rating	IP67, when threaded in
Storage temperature	-25...70 °C

Functional safety

MTTF (40 °C)	58.7 a

Interface

Auxiliary interfaces	8x IO-Link
Conformity class	B
Digital inputs	16x PNP, Type 3
Digital outputs	8x PNP
IO-Link version	1.1.3
Interface 01	Profinet / EtherNet/IP
Interface IIoT	REST API, MQTT
Netload class	III
Port-class	Type A

Material

Gasket, material	FKM NBR
Housing material	PC, injection molding

Mechanical data

Dimension	59 x 36.8 x 180 mm
Mounting ground strap	M4
Mounting part	2-hole screw mount
Weight	180 g


Remarks

See short guide


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.


Connector Drawings



Power IN
PIN 1: L+ (US+)
PIN 2: n.c.
PIN 3: L- (US-)
PIN 4: n.c.



IO-Link
PIN 1: L+ (US+)
PIN 2: I (DI)
PIN 3: L- (US-)
PIN 4: C/Q (SIO/IO-Link)
PIN 5: n.c.



Ethernet
PIN 1: TD+
PIN 2: RD+
PIN 3: TD-
PIN 4: RD-