
Inductive Sensors

BES M12MF1-PSC10F-S04G
Order Code: BES02WR



Basic features

Approval/Conformity	CE cULus WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Inductive sensor

Display/Operation

Function indicator	yes
Power indicator	no

Electrical connection

Connection	M12x1-Male, 3-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at Ue	1.5 µF
Min. operating current Im	0 mA
No-load current Io max., damped	11 mA
No-load current Io max., undamped	7 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	47.0 kOhm
Protection class	II
Rated insulation voltage Ui	250 V AC
Rated operating current Ie	200 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	35 ms
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	15 %
Switching frequency	600 Hz
Utilization category	DC -13
Voltage drop static max.	1.3 V

Environmental conditions

Ambient temperature	-25...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g_n, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP68, according to BWN Pr 20

Functional safety

MTTF (40 °C)	625 a

Interface

Switching output	PNP normally open (NO)

Inductive Sensors

BES M12MF1-PSC10F-S04G
Order Code: BES02WR

Material

Housing material	Brass, Nickel-free coated
Material sensing surface	PBT

Mechanical data

Dimension	Ø 12 x 60 mm
Installation	non-flush
Mounting length	40.00 mm
Size	M12x1
Tightening torque	10 Nm

Range/Distance

Assured operating distance Sa	8 mm
Hysteresis H max. (% of Sr)	15.0 %
Rated operating distance Sn	10 mm
Real switching distance sr	10 mm
Repeat accuracy max. (% of Sr)	5.0 %
Switching distance marking	■■■
Temperature drift max. (% of Sr)	10 %
Tolerance Sr	±10 %


Remarks

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

