**M12 female 90° A-cod. with cable shielded**

PUR 5x0.34 shielded gy 10m

Art.No.: 7000-13281-3491000
Weight: 0,613 kg
Country of origin: CZ
Model designation: MSDL0-U349_10.0-ZE

**Advantages of our connectors:**

Our connectors are versatile and specially optimised for industrial environments. All connectors are 100% tested during the manufacturing process to ensure the highest quality and reliability.

The contacts are gold-plated, which ensures optimum conductivity. Thanks to the high degree of protection, the connectors are ideal for demanding industrial environments. They are also vibration-resistant - this is ensured by the union nut with vibration protection.

Our connectors are resistant to oils and cooling lubricants, but resistance to aggressive media should be tested for each specific application. Different cable lengths available on request


If you are missing technical information? Please feel free to use our dictionary to find more technical details.


**Product details:**

Female 90°
M12, 5-pole
Shielded
with cable sleeves
Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.
Further cable lengths on request.


## Link to Product


**Illustration**








The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14



Product may differ from Image

| | |
|---|---|
| Cable length | 10,00 m |
| **Side 1-1** | |
| Family construction form | M12 |
| No. of poles | 5 |
| Coding | A |
| Gender | female |
| Mounting method | inserted, screwed |
| Threaded hole | M12 x 1 |
| Tightening torque | 0.6 Nm |
| Width across flats | SW13 |
| Cable outlet | angled |
| Material | PUR |
| Material contact | Copper alloy |
| Coating contact | gold plated |
| Degree of protection (EN IEC 60529) | IP67, IP66K, IP65 |
| **Side 2-2** | |
| Family construction form | free cable end |
| Stripping length (jacket) | 20 mm |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

| | |
|---|---|
| **Commercial data** | |
| URL Webshop | https://shop.murrelektronik.com/7000-13281-3491000 |
| EU-Customs tariff number | 85444290 |
| US-Customs tariff number | 8544429090 |
| ETIM-9.0 | EC001855 |
| ETIM-10.0 | EC001855 |
| customs tariff number | 85444290 |
| EAN | 4048879198882 |
| Packaging unit | 1 |
| **Electrical data \| Supply** | |
| Operating voltage AC max. | 60 V |
| Operating voltage DC max. | 60 V |
| Current operating per contact max. | 4 A |
| **Diagnostics** | |
| Status indication LED | No |
| **Installation \| Connection** | |
| Mounting set | M12 x 1 |
| **Device protection \| Electrical** | |
| Additional condition protection degree | inserted, screwed |
| Pollution Degree | 3 |
| Rated surge voltage | 1.5 kV |
| Material group (IEC 60664-1) | I |
| **Mechanical data** | |
| Contour for corrugated hose | without |
| **Mechanical data \| Material data** | |
| Screw connection | Zinc die-casting |
| Coating of fitting | nickel plated |
| Gasket | FKM |
| **Mechanical data \| Mounting data** | |
| Mounting method | inserted, screwed, Shaking protection |
| **Environmental characteristics \| Climatic** | |
| Operating temperature min. | -30 °C |
| Operating temperature max. | 85 °C |
| Additional condition temperature range | depending on cable quality |
| **Important installation notes** | |
| Note on bending radius | **Attention:** Observe the permissible bending radii when laying cables, as the IP protection class can be endangered by excessive bending forces. |
| Note on strain relief | Protect the connectors by suitable measures from mechanical loads, e.g. by the usage of cable ties. |
| **Conformity** | |
| Product standard | EN IEC 61076-2-101 (M12) |
| **Installation \| Cable-1** | |
| Cable identification | 349 |
| Cable weigth | 54 g/m |
| Stranding | 1 Wires |
| Cable shielding (type) | copper braid, tinned |
| Cable shielding (coverage) | 85 % |
| Banding | Fleece, Foil |
| Filler | Yes |
| Wire arrangement | BN, BK, BU, WH, GNYE |
| Shield | shielded |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14

| | |
|---|---|
| Material wire insulation | PVC |
| Amount wires | 5 |
| Outer diameter insulation | 1.45 mm ± 0.05 mm |
| Conductor crosssection (wire) | 0.34 mm² |
| Material conductor wire | Stranded copper wire, bare |
| Core construction (wire) | 42 × 0.1 mm |
| Material properties wire insulation | good machinability |
| Ingredient freeness wire insulation | lead-free, cadmium-free, CFC-free, silicone-free |
| Material jacket | PUR |
| Outer-diameter (jacket) | 5.9 mm ± 5 % |
| Jacket Color | gray / RAL 7001 |
| Material inner jacket | PVC |
| Color (inner jacket) | gray |
| Freedom from ingredients (jacket) | lead-free, cadmium-free, CFC-free, halogen-free |
| Material property (jacket) | abrasion-resistant, low adhesion, good machinability, matte |
| Cable shielding (type) | copper braid, tinned |
| Cable shielding (coverage) | 85 % |
| Conductor resistance (wire) | 57 Ω/km @ 20 °C |
| Max. rated voltage (conductor - ground) | 300 V |
| Max. rated voltage (conductor - conductor) | 350 V |
| Withstand voltage (wire - wire) | 2 kV @ 60 s |
| Withstand voltage (wire - jacket) | 2 kV @ 60 s |
| Withstand voltage (wire - shield) | 1.5 kV @ 60 s |
| Current load capacity max. (wire) | 4.5 A |
| Current load capacity (standard) | to DIN VDE 0298-4 |
| Operating temperature (static) | -40 °C … 80 °C |
| Operating temperature (dynamic) | -5 °C … 70 °C |
| Other resistances | resistant to hydrolysis, resistant to microbes |
| Notes | application-related testing |
| Bending radius (fixed) | 10 × Outer diameter |
| Bending radius (dynamic) | 15 × Outer diameter |
| No. of bending cycles (C-track) | 0.1 Mio. @ 25 °C |
| Traversing distance (C-track) | 5 m @ 25 °C |
| Travel speed (C-track) | 3 m/s @ 25 °C |
| Acceleration (C-track) | 3 m/s² @ 25 °C |

The information in this Product-PDF has been compiled with the utmost care.
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 2026-10-14